


Netdisco



[[Network Map](#)]

[[Device Search](#)]

[[Device Inventory](#)]

[[Node Search](#)]

[[Port Report](#)]

[[Layer 2 Traceroute](#)]

[[Duplex Mismatch Finder](#)]

[[Node Inventory](#)]

[[Backend Log](#)]

[[Documentation](#)]

[[Administration Panel](#)]

[[About](#)]

User maurin

[[Logout](#)]

[[Change Password](#)]

### Device Port Control

Port : [192.168.1.61](#)[FastEthernet0/1]

User : [maurin](#) at 192.168.0.7  
Tue Apr 4 19:39:59 2006

Reason :

See below for descriptions.

Log:

Enter a useful description why the port is being turned off.

Debug

*Note:* This can take up to 1 minute. Do not hit refresh on your browser.

#### Reason Descriptions

Reason	Description
<b>address</b>	A system which does not obtain and/or use its address in a legitimate fashion. This includes machines that self-assign IP addresses and those that modify their MAC address.
<b>bandwidth</b>	A user has sent/received data in excess of campus acceptable use standards.
<b>compromised</b>	The system has been compromised and poses a high risk to campus resources. If other behavior is observed, such as involvement in a DoS attack, that reason code should be used in place of this one.
<b>copyright</b>	Following the takedown provision of the DMCA to limit the University's copyright liability.
<b>dos</b>	Any kind of data flow, malicious or otherwise, which is involved in a service-affecting disruption. This includes activities such as ICMP and UDP floods, SYN attacks, and other service disruptive flows. A system involved in a DoS attack is usually compromised.
<b>exploit</b>	A remotely exploitable vulnerability posing high risk exists on the system.
<b>other</b>	Does not fit in any other category. Make a <i>very</i> detailed Log entry.
<b>polling</b>	Distinct from DoS attacks, excessive polling is often due to misconfigured systems or